

ROULEMENTS DE PALIER HAUTE TEMPERATURE

Référence	Dimensions (mm)								Charge dynamique Kn	Charge statique Kn
	d	D	Bi	Be	n	m	G	ds		
UC201 ZZ 270°C	12	47	31	17	12.7	18.3	4.8	M6X1.0	10	6.30
UC202 ZZ 270°C	15	47	31	17	12.7	18.3	4.8	M6X1.0	10	6.30
UC203 ZZ 270°C	17	47	31	17	12.7	18.3	4.8	M6X1.0	10	6.30
UC204 ZZ 270°C	20	47	31	17	12.7	18.3	4.8	M6X1.0	10	6.30
UC205 ZZ 270°C	25	52	34	17	14.3	19.7	5.5	M6X1.0	11	7.10
UC206 ZZ 270°C	30	62	38.1	19	15.9	22.2	6	M6X1.0	15.20	10.20
UC207 ZZ 270°C	35	72	42.9	20	17.5	25.4	6.5	M8X1.0	20.10	13.90
UC208 ZZ 270°C	40	80	49.2	21	19	30.2	8	M8X1.0	25.60	18.10
UC209 ZZ 270°C	45	85	49.2	22	19	30.2	8	M8X1.0	25.60	18.10
UC210 ZZ 270°C	50	90	51.6	24	19	32.6	10	M10X1.0	27.50	20.20

